

# Huebsch

## Huebsch

### 50 & 75 lb. Coin-Operated Extra Large Capacity Drying Tumblers



*Huebsch understands that getting increased use of you large washers can be a big boost to your laundry's bottom line. Our **EXTRA LARGE** capacity **50lb. and 75lb. drying tumblers** can handle your customer's biggest wash loads with ease.*

***BIG DRYERS**, like big washers, are terrific for items like comforters and sleeping bags, which can help you attract more customers. They are real **business builders!***

*Serving the Laundry Industry For Over 90 Years*



# 50 & 75 lb. Coin-Operated Drying Tumblers Specifications

## Construction & Features

Huebsch dryers feature an **all belt drive system** with a self adjusting tension idler. The drive system is constructed with metal pulleys and permanently sealed bearings for super quiet operation and low maintenance.



## Your Choice of Controls



### Programmable Electronic Control—

*with vend price display and time count down*



### Electromechanical Control—

*with rotary coin drop*



Our doors are constructed of top-quality **stainless steel** to stand-up to the use in the toughest laundry environments. Many others use plastic for this important part, not Huebsch!

Huebsch tumblers feature a **self-cleaning lint screen** made of fine mesh. Lint is deposited into a large storage area for easy removal. This helps maintain maximum airflow and promotes fast efficient drying.



## Additional Features

- Galvanized steel cylinder for long life
- Optional stainless steel cylinder
- Integrated motor overload protection
- Solid steel cap over top of the dryer
- Embossed steel cabinet for easy cleaning
- All major components easily accessible
- High temperature limit control

|  | 50#                             | 75#                             |
|--|---------------------------------|---------------------------------|
| <b>Width (in./mm)</b>                            | 38.62" (981 mm)                 | 38.62" (981 mm)                 |
| <b>Depth (in./mm)</b>                            | 47" (1194 mm)                   | 53" (1346 mm)                   |
| <b>Height (in./mm)</b>                           | 76.62" (1946 mm)                | 76.62" (1946 mm)                |
| <b>Cylinder Depth (in./mm)</b>                   | 30" (762 mm)                    | 36" (914 mm)                    |
| <b>Cylinder Diam. (in./mm)</b>                   | 37" (939 mm)                    | 37" (939 mm)                    |
| <b>Cylinder Vol.</b>                             | 18.67 cu. ft. (528.8 liters)    | 22.40 cu. ft. (634.4 liters)    |
| <b>Door Opening</b>                              | 22.68" (576 mm)                 | 22.68" (576 mm)                 |
| <b>Dry Weight Capacity</b>                       | 50 lb. (22 kg)                  | 75 lb. (33.9 kg)                |
| <b>Airflow</b>                                   | 750 CFM (354 liters/sec)        | 920 CFM (434 liters/sec)        |
| <b>Energy Data and Electrical Specifications</b> | <b>Gas Model</b>                | <b>Gas Model</b>                |
|  | 120,000 Btu/hr (30,240 kcal/hr) | 165,000 Btu/hr (41,580 kcal/hr) |
|  | <b>Amps</b>                     | <b>Amps</b>                     |
|  | 120/60/1 9.3 -                  | 120/60/1 13.8 -                 |
|  | 200-208/240/60/1 5.1 -          | 200-208/240/60/1 7.6 -          |
|  | 230-240/50/1 6.3 6.9            | 230-240/50/1 6.7 7.0            |
|  | 200-208/240/60/3 2.8 4.0        | 200-208/240/60/3 3.8 4.3        |
|  | 200/50/3 3.3 4.2                | 200/50/3 3.5 4.5                |
| 230-240/50/3 3.1 4.3                             | 230-240/50/3 3.5 4.9            |                                 |
| 380/400-415/50/3 1.6 2.0                         | 380/400-415/50/3 1.8 2.1        |                                 |
| 460-480/60/3 1.4 1.9                             | 460-480/60/3 1.9 2.1            |                                 |
| <b>Plumbing Connection</b>                       | 1/2" - NPT                      | 1/2" - NPT                      |
| <b>Net Weight</b>                                | 545 lb. (247 kg)                | 615 lb. (279 kg)                |
| <b>Shipping Wt. (Domestic)</b>                   | 602 lb. (273 kg)                | 677 lb. (307 kg)                |
| <b>Shipping Dimensions (Domestic) (in./mm)</b>   | Width - 41.5" (1054 mm)         | Width - 41.5" (1054 mm)         |
|  | Depth - 52.1" (1323 mm)         | Depth - 56.4" (1433 mm)         |
|  | Height - 81" (2057 mm)          | Height - 81" (2057 mm)          |

Tumbler models are made to suit a variety of electrical service characteristics. See your Huebsch distributor for specifications. For further details on installation refer to Installation, Operation and Maintenance instructions supplied with the tumbler. Due to continuous product improvements, design and specifications subject to change without notice. Gas models are certified by the American and Canadian Gas Association. The quality management systems at all Alliance Laundry Systems facilities have been awarded ISO 9001 certification.



## Unmatched Warranty

At Huebsch, we're so confident that our quality drying tumblers are built to last, we offer a **THREE** year warranty\* on the entire machine.

\*Parts only, labor not included. See Huebsch Warranty Bond for specifics.

